

NINJA LUXE CAFÉ

Owner's Guide

IMPORTANT SAFETY INSTRUCTIONS

PLEASE READ CAREFULLY BEFORE USE • FOR HOUSEHOLD USE ONLY

- Read all instructions before using your Ninja Luxe Café.
- Indicates the presence of a hazard that can cause personal injury, death or substantial property damage if the warning included with this symbol is ignored.
- Avoid contact with hot surface. Always use hand protection to avoid burns.
- For indoor and household use only.

WARNING

To reduce the risk of injury, fire, electrical shock or property damage, basic safety precautions must always be followed, including the following numbered warnings and subsequent instructions. Do not use machine for other than intended use.

- General Precautions**
- To eliminate a choking hazard for young children, discard all packaging materials immediately upon unpacking.
 - This machine can be used by persons with reduced physical, sensory, or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the machine in a safe way and understand the hazards involved.
 - Keep the machine and its cord out of reach of children. **DO NOT** allow the machine to be played with or be used by children. Close supervision is necessary when used near children.
 - To protect against fire, electric shock, and injury to persons, **DO NOT** immerse cord, plugs, or body of machine in water or other liquid.
 - NEVER** carry the machine by the power cord or pull it to disconnect from electrical socket; instead grasp the plug and pull to disconnect.
 - DO NOT** operate any machine with a damaged cord or plug, or after the machine malfunctions or has been dropped or damaged in any manner. Contact a service center.
 - For household and countertop use only. **DO NOT** let the power cord hang over the edge or touch hot surfaces such as a stove.
 - NEVER** use an electrical socket below a counter.
 - To avoid risk of fire, electrical shock, or damage to the machine, **DO NOT** use machine in machine garage or under a wall cabinet.
 - Unplug from outlet when the machine is not in use and before cleaning.
 - NEVER** leave machine unattended while in use.
 - Machine is not intended to be operated by means of an external timer or separate remote-control system.
 - DO NOT** place on top of any other machine.
 - The machine shall not be placed in a cabinet when in use.
 - DO NOT** use any accessory not recommended by the manufacturer, as this may result in injury or damage to the machine.

- Operating Notice**
- Power the machine off and unplug from the wall outlet.
 - The use of an accessory not recommended by the manufacturer may create an overflow condition and scalding hazard, or result in fire, electric shock, or personal injury.
 - ALWAYS** use machine on a clean, dry, level surface.
 - DO NOT** place on or near a hot gas or electric burner or in a heated oven.
 - DO NOT** use this machine for anything other than its intended use.
 - DO NOT** use outdoors.
 - DO NOT** touch hot surfaces. Use handles or knobs. Avoid contacting moving parts.
 - ALWAYS** place a cup or vessel appropriate for output volume selection beneath the portafilter when brewing.
 - DO NOT** run the machine without water.
 - DO NOT** overfill the water reservoir. Fill water only to the maximum fill line.
 - Keep lid on water reservoir when brewing.
 - Keep bean hopper lid on when grinding to prevent access to moving parts.
 - DO NOT** remove portafilter when brewing as machine is under pressure. Removal while brewing can lead to scalding or injury.
 - DO NOT** reach in or touch steam wand or frother jug when in operation. Hot steam and hot liquids will cause burns and scalds.

- Care & Maintenance**
- To prevent illness from bacterial growth in the machine, follow all cleaning instructions in the Cleaning & Maintenance section of this Owner's Guide.
 - For best results, ensure you are using a clean machine.
 - If the product is not operating properly, contact a service center.
 - Children shall not engage with cleaning and maintenance activities.
 - When portafilter is in use, ensure it is tightened in the group head to prevent spillover of hot liquid.
 - DO NOT** pick up the machine by the grinding cradle. This apparatus is not meant to hold weight of product.

- Cord Statement**
- A short power-supply cord is provided to reduce the risks resulting from becoming entangled in or tripping over a longer cord.
 - DO NOT** use extension cords with this product.

READ AND SAVE THESE INSTRUCTIONS

TECHNICAL SPECIFICATIONS	NOTE:
Voltage: 120V~60Hz Power: 1650W Water Reservoir Capacity: 70 oz.	In order to ensure the highest possible standard for refurbished items, all units are thoroughly inspected as part of the process. For this item, water may be used during the refurbishing process and so; you may notice some condensation in the water reservoir. It is recommended to rinse the water reservoir with fresh water prior to its first use.

ASSEMBLY

Scan for easy 3D instructions

Tap, Zoom, Rotate with official interactive instructions on the BILT app.




PRINTED IN MEXICO
Elbrd: J.M. SC: 09-19-2025
OBPN: ES601_IB_43_REV_Mv34_250214
SHDML: ES601GM_B

814100591


PARTS

- A Bean Hopper
- B Water Reservoir
- C Cup Warmer
- D Control Panel
- E Accessory Storage
- F Steam Wand
- G Group Head
- H Milk Jug with Integrated Whisk
- I Adjustable Cup Tray
- J Grinding Cradle
- K Main Drip Tray
- L Assisted Tamer Storage
- M Funnel Storage
- N Grind Dial
- O Integrated Conical Burr Grinder




DRIP TRAY COMPONENTS

- K Main Drip Tray
- K1 Empty Indicator
- K2 Main Grate
- K3 Center Drip Tray
- K4 Center Grate
- K5 Milk Jug Platform



ACCESSORIES


- 1 Double Basket
- 2 Luxe Basket
- 3 Portafilter
- 4 Cleaning Disc
- 5 Cleaning Brush
- 6 Funnel
- 7 Assisted Tamer
- 8 Cleaning Tablets
- 9 Descale Powder
- 10 Water Hardness Test Strip



NOTE: CLEAN BEFORE USE

USING THE CONTROL PANEL

- A POWER Button
- B START GRIND Button
- C Progress Bar
- D Froth Dial/START FROTH Button
- E PURGE Button
- F CLEAN Button
- G MILK TYPE Button
- H SIZE Selection Button
- I Center Dial/START BREW Button
- J STRENGTH Button
- K DESCAL Button



*Functions may vary by model.

INTELLIGENT NOTIFICATIONS

The machine will display an intelligent notification if an action is needed:

- ADD BEANS
- INSTALL PORTAFILTER
- INSTALL FUNNEL
- INSTALL HOPPER
- ADD WATER
- INSTALL JUG
- RINSE
- PURGE
- DESCAL*
- CLEAN*

*The CLEAN and DESCAL buttons will illuminate to let you know you need to run the respective cycle.

NOTE: The actual descriptions of control panel and their locations may vary depending on the model.

GETTING STARTED: BEFORE YOUR FIRST BREW

REMOVE ACCESSORIES & PARTS FROM PACKAGING

- To start, remove all accessories and parts from packaging. Ensure that all accessories and parts are removed from the packaging before discarding packaging.
 - When removing the machine from packaging, be sure to remove all tape from machine. Tape will be on all sides of the machine.
- CLEAN ACCESSORIES BEFORE USE**
- After removing all accessories and parts from the packaging, thoroughly clean all parts by hand-washing and dry thoroughly.

WATER HARDNESS TEST

All water has minerals that can cause buildup in the machine over time. These minerals are referred to as water hardness, and will impact how often you will need to descale the machine. Doing this test will ensure the machine recommends a descale at the right time.

- Remove test strip from pack.




- Completely submerge the water test strip in the water you plan on using with the machine for 5-10 seconds.




- Pull test strip out and lightly shake it.



- Place test strip on a dry, flat surface and wait 1 minute for test strip to display results.
- After 1 minute, you will see 0-5 purple squares appear. This will indicate the water hardness level of the water (0 purple squares=level 0, 5 purple squares=level 5, etc.)



- After identifying the water hardness level, plug in the machine.
- Look at the left side of the control panel. It will display hd 5.
- Rotate the center dial to program the water hardness level by matching the number of purple squares on the test strip to the number displayed. (e.g., if the result is level 1, change the setting to hd 1).




- Press center dial to confirm your setting.

NOTE: For more instructions on how to reset the water hardness, refer to the Additional Settings section.

FILL THE WATER RESERVOIR

- Before you begin, make sure the water reservoir is full of room-temperature or cold water. Be sure to fill up to but not exceeding the maximum fill line.




If at any point before a brew there's not enough water in the reservoir to brew your selected drink, the machine will indicate that you must ADD WATER. If you get an ADD WATER notification while brewing, add water to the reservoir and press START BREW to resume.


BREWING ESPRESSO, DRIP COFFEE, AND COLD DRINKS

ESPRESSO/COFFEE BASKETS

- The Starter Kit contains the baskets. There are three baskets (single, double, and luxe baskets may vary per model).




- Choose a basket based on what drink you would like, then insert into the portafilter. Ensure that the large tab on the basket aligns with the large tab on the portafilter, and then press firmly into place.



NOTE: Double basket comes pre-installed in portafilter.

PORTAFILTER INSTALLATION

- Place funnel on portafilter, aligning the notches on the funnel with the notches on the portafilter. Push down until funnel locks into place in the portafilter. The funnel prevents grounds from overflowing during grinding and allows for a cleaner tamping process.



- With the funnel on top of the portafilter, insert into the grinding cradle. Make sure it is level and fits securely. Once portafilter is installed in grinding cradle, it will be weighed. To ensure accurate weight, let go of portafilter.



- The machine will detect which basket is locked into it. The machine will display an animation. This is to indicate the machine is taring the portafilter to ensure it is dispensing the right amount of grounds. Then the control panel will illuminate the selectable brew options based on the basket that is installed.



NOTE: If you do not see this animation, remove the portafilter from the grinding cradle, power the machine off and on, and reinstall the portafilter in the grinding cradle, ensuring it is level and pushed all the way in.

- Turn the center dial to your desired brew.

ADJUSTING YOUR BREW TEMP AND STRENGTH

ADJUSTING BREW TEMPERATURE

- Hold the SIZE button for 3 seconds.
- Rotate the center dial to _h06, then press the center dial to select.
- Rotate the center dial to select your desired setting, then press the center dial to select.

LO: Low temperature
M: Medium temperature (default)
HI: High temperature.

The temperature of the drink will affect the extraction of the espresso and the flavor of your drink. For best results and proper extraction, we recommend a low or medium temperature for darker roasts, and a medium or high temperature for light roasts.

NOTE: Temperature control not available for over ice, cold brew, and cold-pressed.

APPROXIMATE BREW VOLUMES

	COFFEE VOLUMES	
	Classic Rich	Over Ice Cold Brew (Must Fill with Ice Before Brewing)
SIZES	6 oz.	6 oz.
	8 oz.	8 oz.
	10 oz.	10 oz.
	12 oz.	12 oz.
	14 oz.	14 oz.
	16 oz.	16 oz.
	18 oz.	18 oz.

Outputs may vary by +/- 10%



	ESPRESSO VOLUMES	
	Grounds Dose	Output Volume
Single Espresso	9 g	0.8 oz.
Double Espresso	18 g	1.5 oz.
Double Cold-Pressed	18 g	1.5 oz.
Quad Espresso	40 g	3.5 oz.
Quad Cold-Pressed	40 g	3.5 oz.

Outputs may vary by +/- 10%

NOTE: These are the preset espresso outputs. To adjust output, please refer to the Additional Settings section.

USING THE GRINDER

- Once a brew is highlighted, Barista Assist Technology™ will recommend a grind size based on the beans and previous brew output. If you wish to follow the recommended size, use the grind dial on the side of the machine to change the **CURRENT** grind size to match the **RECOMMENDED** grind size.



- Once you have selected your desired grind setting, press START GRIND to begin grinding. The machine will beep to indicate that grinding has started. When finished, the machine will beep again signifying grinding is complete. The control panel will flash TAMP, signifying that you must tamp the grounds.

NOTE: Once a grind is complete, the machine will be set to the brew style and size that was selected for that grind. To change style and size, pour grounds out of portafilter, power the machine off and on, and select your desired brew.

UNDERSTANDING THE GRIND SETTINGS

What do the grind settings mean?

- The numbers on the left side of the control panel represent how coarse or fine the grind will be, with 25 being the coarsest and 1 being the finest. Coarser settings will work better for coffee drinks, and finer settings will work better for espresso drinks.
- Matching the recommended setting: this will bring the best flavors out of your chosen beans. The machine will adjust based on what beans you're using to ensure you are not over extracting or under extracting.

DIALING IN THE GRINDER FOR PROPER EXTRACTION

For espresso brews only

You may notice the recommended grind setting change. This is Barista Assist Technology adjusting the recommended grind setting to help you get proper espresso extraction. When using new beans for the first time or adding more beans, it may take 2-3 brews to reach the optimal grind setting. Over time, you may notice the recommended grind setting change to account for aging beans. This is normal. Ensure the current grind size matches the recommended grind size for proper espresso extraction.


NOTE: When changing from very coarse to very fine (or vice versa), you may hear the grinder turn on. This is to help prevent jamming in the grinder. This will only happen when the portafilter is installed in the grinding cradle.

TAMPING

Be sure to tamp on all espresso drinks, as well as 16 oz. and 18 oz. coffee drinks; this is to ensure no grounds spill over the edge of the portafilter. For 6 oz. to 14 oz. coffee drinks, lightly shake the portafilter to level coffee grounds and then proceed to brewing.




- When grinding is complete remove the portafilter from the grinding cradle. Keep the funnel attached to the portafilter.
- Place the portafilter on a solid, level surface, then place the assisted tamer inside the funnel. Ensure there is protection between the portafilter and surface. Press tamer all the way down until it meets the funnel.



NOTE: If tamping on top of a wooden or delicate material countertop, put towel down for protection.

NOTE: When brewing a quad shot, tamp the grounds normally with the funnel on the portafilter. After that, remove the funnel and tamp down the grounds one more time.


- Now that tamping is complete, remove both the tamer and funnel from the portafilter and store in their respective locations on the left side of the machine.



To avoid the RINSE process, brew all desired cold drinks before proceeding to hot drinks.

BREWING

- Place portafilter in group head by aligning orange dot on portafilter with orange dot on group head.
- Fasten portafilter into group head until orange dot on portafilter aligns with lock arrow on group head.



NOTE: DO NOT brew without the main drip tray inserted.

- The brew style and size that was ground will still be selected on the control panel. Place a cup under the portafilter and press START BREW.
- The machine will beep to indicate that the brew has started. The progress bar will illuminate indicating the status of the brew. When finished, the machine will beep again signifying the brew is complete.

NOTE: If you are using a smaller cup, use the adjustable cup tray to lift your cup closer to the group head to reduce splatter. If you are using a larger mug or travel mug, remove the center drip tray to create space.

NOTE: For quad espresso shots and quad cold-pressed shots, there may be some water on the puck after brewing. This is normal.


PROPER EXTRACTION

- Drink will pour out at a slow, consistent rate.
- You will see a caramel-colored liquid pouring out. That is the crema.
- There will be a layer of crema on top of your drink. Feel free to tilt your cup to see if the layer of crema is still completely visible. If you can still only see that caramel color, you have a properly extracted espresso shot.



AFTER YOUR BREW

When brew is complete, carefully remove portafilter from group head. Dispose of grounds by knocking the surface of the basket over a container or knock box (sold separately).



RINSE NOTIFICATION

If you attempt to make a cold drink immediately after making a hot drink, you will get a RINSE notification above the center dial.

Be sure that the portafilter is not installed in the group head before proceeding.

- Put a cup (that can hold at least 12 oz.) below the group head.
- Press START BREW and allow the machine to rinse and get to the right temperature.
- The machine will rinse approximately 8 oz. of water through the group head.
- The machine will beep to indicate that the brew has started. The progress bar will illuminate indicating the status of the brew. When finished, the machine will beep again signifying the brew is complete. After the machine beeps a second time, remove the cup and dispose of the water.

To avoid the RINSE process, brew all desired cold drinks before proceeding to hot drinks.

Espresso Strength Adjustments:

- Taller, less concentrated: 4:1 water to grounds ratio.
- Default: 2.5:1 water to grounds ratio.
- Shorter, more concentrated: 2:1 water to grounds ratio.

NOTE: Adjusting your espresso brew strength will affect your brew volume output. Strength 1 will have a larger output than the default setting. Use a larger cup than normal.

- Coffee Strength Adjustments:
- Mild: Less beans will be ground
- Default
- Bold: More beans will be ground

COFFEE FLAVOR ADJUSTMENT

Barista Assist will recommend a grind size depending on brew style and size. Because not all beans are roasted the same, with the grind dial you have the opportunity to adjust the flavor profile.

Less Bitter: Decrease Grind Size

Less Sour: Increase Grind Size

SWITCHING OUT BEANS

It is recommended to clean out the grinder before switching beans. Please see instructions on how to clean the grinder in the "Cleaning the Conical Burr Grinder" Maintenance section.

SWITCHING OUT BEANS

- 1 Unlock bean hopper by rotating handle counterclockwise.
- 2 Remove the bean hopper and pour out any leftover beans.
- 3 Place the hopper back on the machine.
- 4 Lock bean hopper back in by rotating handle clockwise.



NOTE: When out of water, the machine will not purge. Be sure to press the PURGE button when adding more water in to complete purge.


- 5 Place the portafilter with the funnel attached in the grinding cradle.
- 6 Press and hold START GRIND button to clear any leftover beans.
- 7 Add new beans into the bean hopper.

NOTE: For best practice, if changing bean or roast type, reset Barista Assist Technology using the instructions in the "Additional Settings" menu, prior to dialing in the new beans.

FROTHING

FROTHING

- 1 Fill the milk jug with the desired amount of milk, but do not exceed the max fill line. Ensure that whisk is installed.



- 2 Ensure that the bottom of the milk jug is dry. Place the milk jug on the milk jug platform with the steam wand inserted into the milk jug.



- 3 On the control panel, use the froth dial to highlight the desired froth style.



FROTH STYLES

Steamed Milk
Gently steam milk to an ideal drinking temperature without whisking. Great for coffee.

Thin Froth
A thin layer of foam for lattes.


Thick Froth
A classic layer of fluffy froth to top any drink. Great for cappuccinos.

Extra-Thick Froth*
A large layer of froth, ideal for cappuccinos and other drinks with less volume.

Cold Foam
A classic layer of cold froth to top any iced coffee or espresso drink.

*Not available on all models.

- 4 Next, select DAIRY or PLANT-BASED milk with the MILK TYPE button based on the milk that is in the milk jug. Press START FROTH. The machine will beep to signal that the frothing has started. The progress bar will illuminate to indicate the status of the frothing. The machine will beep again to signify the froth is complete.




NOTE: DO NOT froth milk directly into the espresso or coffee, always froth in the milk jug and pour the froth into the espresso or coffee base afterwards.

NOTE: DO NOT froth without the main drip tray inserted.

NOTE: If you would like to change the temperature of your froth, see Additional Settings.

AFTER YOU FINISH FROTHING

- 1 Once you remove the milk jug, immediately wipe the steam wand with a damp cloth before pushing it back down into its down position.



- 2 When the steam wand is pushed back into its down position, auto purging will occur. This is to clean the inside of the steam wand. The machine will beep to signal that the purge has started. When finished, the machine will beep again. You can purge at any time by pressing the PURGE button when steam wand is in down position.



- 3 Before pouring milk, tap the jug on a flat surface and swirl around to remove large bubbles. Pour frothed milk over espresso or coffee and enjoy.



FROTH QUEUING


After you have started your brew, you are able to queue up your froth to start immediately after the brew is finished.

- 1 Fill the milk jug with the desired amount of milk, but do not exceed the max fill line.
- 2 While brewing, select DAIRY or PLANT-BASED milk with the MILK TYPE button and froth setting with the froth dial.
- 3 Press START FROTH.

Cold foam  does not need to be queued and can froth while the machine is brewing.


MANUAL FROTHING

- 1 Fill the milk jug as desired in between the min and max fill lines.
- 2 Make sure you are on the steamed milk setting .
- 3 Pull the steam wand out. Place the steam wand inside the milk jug so that the wand is resting on the milk jug spout.
- 4 Angle the milk jug slightly to the left or right so that the steam wand is about a finger's width away from the wall of the milk jug.



- 5 Hold START FROTH for 3 seconds. The machine will beep to indicate that frothing has started and steam will start to generate from the wand.

- 6 Place wand just below the surface of the milk to start incorporating air to stretch the volume milk. This should start to create a whirlpool with the milk.



- 7 Once you feel comfortable with the volume of milk, move the jug up so the steam wand is further below the surface. This is to heat your drink up.
- 8 Stay in that position until the jug is too hot to hold with your hand, then press START FROTH to turn the function off.

PERIODIC MAINTENANCE

IMMEDIATELY AFTER BREW CLEANING

- When brew is complete, carefully remove portafilter from group head. Dispose of grounds by knocking the surface of the basket over a container or knock box (sold separately).
- For best results, be sure to clean out the portafilter and basket between each use.
- Remove basket from portafilter. Hand-wash both items with soapy water to remove all coffee oils. Be sure basket is dry before brewing again.

- After you froth, wipe the wand with a damp cloth before pushing it back into its down position.
- Push steam wand into its down position to initiate an auto purge.
- Empty the drip tray when the orange empty indicator rises enough to become visible.
- Periodically hand-wash the drip tray and air-dry thoroughly.
- Periodically clean the base of the machine with a damp cloth.

CLEANING THE ACCESSORIES


Dishwasher-Safe Parts:

Funnel, whisk, cleaning disc, water reservoir, bean hopper, and all drip tray components.

NOTE: DO NOT submerge non-dishwasher-safe parts or accessories in water.

EMPTYING THE DRIP TRAY

As you brew, the drip tray will fill up. When the orange empty indicator rises enough to be visible, it's time to empty the main drip tray.



- 1 Remove the main drip tray from the machine by pulling tray away.



- 2 Carefully move the main drip tray to the sink and pour water out through the pour spout.

- 3 Insert drip tray back into the machine.

NOTE: Empty indicator is removable.

NOTE: Remove center drip tray before emptying. Wipe off with a damp cloth separately.

REMOVING THE SHOWER SCREEN AND REPLACING THE RUBBER GASKET

If you notice your brew quality diminish over time, remove the shower screen and clean it thoroughly.


If you experience leaking around the portafilter during a brew when the handle is fully tight, you may need to replace the gasket.

Be sure that the machine is turned off and unplugged before proceeding.

- 1 Using a Phillips-head screwdriver, remove central screw on shower screen, then remove shower screen.

- 2 Once removed, clean the shower screen with soap and water.

- 3 Remove rubber gasket from group head with flathead screwdriver. Inspect gasket for any wear or tearing, and replace with a new gasket if needed.



- 4 Insert shower screen back into group head and secure in position with screw.

CLEANING THE CONICAL BURR GRINDER

To prevent clogging and ensure the highest quality output, it is recommended to clean your conical burr grinder weekly at a minimum for daily use. For dark roast, decaf and other oily bean types, it is recommended to clean the grinder more often. For less than daily use, clean your grinder monthly at minimum or anytime you swap out or refill the beans.

Be sure that the machine is turned off and unplugged before proceeding.

- 1 Remove all beans from the bean hopper. See Switching Out Beans for reference.
- 2 Ensure the bean hopper is installed and locked. Clear out any leftover beans on top of the grinder by performing a "purge", following these instructions. First, set the grind size to 25, and with the portafilter in the grinding cradle, press and hold "start grind". Once grinding begins, continue holding the button for about 10 seconds or until there is a noticeable change in noise. This will grind away and remove any material left in the grinder. If there is still residue left on the burr, sweep it off with the included cleaning brush and perform another purge if necessary.

DESCALING AND CLEAN CYCLE

DESCALING

Time to complete: approximately 90 minutes

NOTE: If using a filter in your water reservoir, please remove it before starting the descale cycle. Water filter housing and inserts sold separately.

- 3 Turn off and unplug the machine. Remove bean hopper by lifting handle and turning to counterclockwise.

- 4 Remove upper burr by rotating counterclockwise, aligning the orange arrow on the burr grinder with the orange arrow labeled ALIGN on the machine. Once aligned, lift upper burr out.

- 5 Clean removed burr grinder with brush.

- 6 Then, clean burr grinder attached to machine with cleaning brush.

- 7 Be sure to clean the inside of the grinding cradle as well.

NOTE: Empty indicator is removable.

NOTE: Remove center drip tray before emptying. Wipe off with a damp cloth separately.


NOTE: DO NOT allow burrs to come into contact with water.

NOTE: When cleaning the burr grinder attached to the machine, only use the cleaning brush.


CLEANING THE STEAM WAND

Over time, material can build up in the steam wand.


- 1 Remove the cap on the bottom of the cleaning brush to access the needle.
- 2 Use the needle to remove any material from the steam wand tip.



- 3 For a deeper clean, use the wrench in the middle of the cleaning brush to remove the steam wand tip.



- 4 Use the needle to remove any material from inside the steam wand and steam wand tip.




- 5 After cleaning, run a purge to clear out any excess material.


When the DESCALE light illuminates, you must run a descale cycle. If a descale isn't performed after the light turns on, drink quality will diminish and the machine may clog and stop working.

Descaling breaks down and removes limescale and mineral buildup inside the machine. Doing this will help maintain peak performance if routinely performed with a descale solution whenever the DESCALE light turns on.

- 1 Ensure the main drip tray is completely emptied, as some of the water brewed from the descale cycle will be deposited into the main drip tray. **Not emptying the main drip tray may cause overflow.**



- 2 Dissolve the provided Ninja descale powder in a separate container with 37 fl. oz. of water. Pour solution mixture into water reservoir.



- 3 Insert the double basket into the portafilter.

- 4 Fasten the portafilter into the group head.
- 5 Ensure milk jug is placed on the milk jug platform with the steam wand inside.
- 6 Place an empty cup (at least 18 oz.) under the portafilter. You may have to remove the center drip tray.

- 7 Press the DESCALE button, then press the center dial to start the descale cycle.
- 8 The machine will start the descale cycle. The machine will flush solution through the steam wand and portafilter for approximately 90 minutes. The machine will count down the remaining time on the control panel.
- 9 The machine will beep indicating when the descale cycle is complete.

- 10 After the cycle is complete, remove the portafilter, main drip tray, and milk jug with caution, as there will be water in each.

- 11 Empty the contents of each and hand-wash with warm soapy water to remove any solution that could affect the flavor of your coffee.

- 12 Fill the reservoir with fresh water up to, but not exceeding, the Max Fill line.

- 13 Install the main drip tray back on the machine and install the portafilter in the group head. Do not install the milk jug.

- 14 Flush the group head by running a 12 oz. CLASSIC brew.

- 15 Then, with the milk jug uninstalled, flush the steam wand by pressing the PURGE button.


RUNNING A CLEAN CYCLE

Time to complete: approximately 6 minutes

A clean cycle flushes out residual oils or grounds that are built up in and around the group head. The CLEAN light will automatically illuminate to indicate when a clean cycle is required. You may also run a clean cycle if you notice a change in brew quality. The clean cycle requires the cleaning disc (included with the machine and storable in the accessory storage) and a cleaning tablet (also included).

Follow these steps to run a clean cycle:

- 1 Ensure the main drip tray is completely empty as the water brewed from the clean cycle will be deposited into the main drip tray. **Not emptying the main drip tray may cause overflow.**



- 2 Fill the water reservoir up to but not exceeding the Max Fill line.

- 3 Insert the double basket in the portafilter.

- 4 Place the cleaning disc on top of the double basket, with the handle facing up.



- 5 Place 1 cleaning tablet in the center of the cleaning disc.



- 6 Fasten the portafilter in the group head.

- 7 Press the CLEAN button, then press the center dial to start the clean cycle.

- 8 The machine will start the process of backflushing the shower screen and group head and depositing the water and sediment from the clean cycle into the main drip tray.

- 9 The clean cycle will take approximately 6 minutes to complete. The machine will beep when the clean cycle is complete.

- 10 After the clean cycle is complete, remove both the portafilter and main drip tray with caution, as there may be water in both. Hand-wash with warm soapy water.

BEST BREWING PRACTICES

- For best results, use freshly roasted coffee beans.
- When purchasing coffee beans, it's best to buy a bag with a "Roasted On" date rather than a "Best Before" date to ensure quality and freshness.
- We recommend you use any coffee beans within 20 days of the "Roasted On" date.
- When changing to a different bean, fully remove previous beans before proceeding. See the Switching Out Beans section for more information.
- Always match the current to the recommended grind setting.
- To increase the brew temperature, run a water flush before making your drink.
- Keep your machine clean by using the brush to wipe off any debris.
- Use filtered water.
- Dial in the grinder whenever switching out beans.
- Keep machine on a stable surface.
- Empty drip tray frequently.
- After you grind and before you start brewing, the machine will start to heat up. Place your mug on the heated cup tray to warm it up.

BEST FROTHING PRACTICES

- For best results with plant-based milk, use the barista or full-fat version.
- For dairy milk, we recommend using whole milk.
- Milks that are UHT-treated (Ultra High Temperature) may have varying results.
- Coconut milk can be heated up but will not make stable froth.
- If you would like to adjust milk temperature, please see Additional Settings section.
- For best results use cold milk or milk out of the refrigerator.
- For best results make sure the milk jug is at room-temperature before frothing.
- Ensure both the milk jug platform and the bottom of the milk jug are dry and clean before placing on the milk jug platform.
- Wipe steam wand with a damp cloth immediately after use to prevent milk from sticking.
- Before turning off the machine, push the steam wand back into the down position to allow it to purge.
- For a deeper clean of the whisk and steam wand, fill milk jug to the max line with water and a drop of dish soap and run the THIN FROTH  program.
- For best foams and latte art, tap and swirl the milk jug prior to pouring milk.
- For best plant-based froth, use the PLANT-BASED setting.

REFURBISHED PRODUCT LIMITED NINETY DAYS WARRANTY

The **Refurbished Product Service Center** offers the following WARRANTY to the ORIGINAL purchaser of a product which we have refurbished.

This product that has been refurbished is warranted against any electronic or mechanical defects for a period of NINETY DAYS from the date of the original purchase by the consumer. Since this unit was sold as a refurbished item, the warranty does not apply to any cosmetic appearance items such as scratches. Should a defect occur, the **Refurbished Product Service Center** will repair or, at its option, replace defective units with new or rebuilt materials without charge for either parts or labor. Replacement units will be warranted for the remaining portion of the original warranty period.

This warranty does not cover installation or damage from accident, misuse, abuse, improper wiring, incorrect voltage, operating the unit against the instructions in the owner's manual or any product which has been opened, altered, or tampered with.

This warranty does not cover costs for removal and/or installation of the unit for repair. Under no circumstances shall the service center be liable for any special, incidental or consequential damages or for any other expenses incurred by reason of use or sale of this product. This warranty is in lieu of any other warranties expressed or implied warranty of merchantability of fitness for particular use or otherwise.

This warranty gives the consumer specific legal rights and they may also have other rights which vary from State to State. Some States do not follow the exclusion or limitation of incidental or consequential damages, hence the above exclusion and limitations may not apply.

Refurbished Product Service Center
9043 Siempra Viva Rd Suite 110/120, San Diego CA, 92154

ADDITIONAL SETTINGS

The additional settings menu offers additional options to customize your machine and is accessible by pressing and holding the SIZE button for 3 seconds.

Item Number	Topic	Options
_h01	Beeps: Turns all beeps on or off.	ON: Leaves beeps on (Default) OFF: Turns beeps off
_h02	Eco Mode: Saves power by turning boiler off after brewing.	ON: Turns Eco Mode on OFF: Leaves Eco Mode off (Default)
_h03	Recommended Grind Size: Turns recommended grind setting display on or off.	ON: Leaves display on (Default) OFF: Turns display off
_h04	Barista Assist Technology™ Reset: Resets recommended grind setting to default setting.	NO: Keeps your current settings (Default) YES: Resets your settings
_h05	Factory Settings Reset: Reset all variables on the machine to default settings.	NO: Keeps your current settings YES: Resets your settings
_h06	Brew Temperature: Adjusts the temperature of your drink.	LO: Low temperature M: Medium temperature (default) HI: High temperature
_h07	Froth Temperature: Adjusts the temperature of your froth.	LO: Low temperature M: Medium temperature (default) HI: High temperature
_h08	Hard Water: Brings the hard water test menu up to reset your water hardness.	hd 0: Strip has 0 purple boxes hd 1: Strip has 1 purple box hd 2: Strip has 2 purple boxes hd 3: Strip has 3 purple boxes hd 4: Strip has 4 purple boxes hd 5: Strip has 5 purple boxes

NOTE: Empty indicator is removable.

- 1 Navigate through these topics by turning the center dial. Press START BREW to select your desired topic.
- 2 Once you select into a topic, turn the center dial to get to your desired option and press START BREW to make your selection.
- 3 After a selection is made, you will hear a beep and return to the menu screen. Please note that the machine will not beep if beeps are turned off.
- 4 You can exit the menu by pressing the SIZE button again.

TROUBLESHOOTING GUIDE

Why is there no water coming out of the portafilter?

- Several factors could affect the volume of water dispensing from the portafilter:
- Not enough water in the reservoir: Ensure the water reservoir is adequately filled. When using the luxe basket, 18 oz. of water is required. When using the double or single basket, fill to the min. line.
 - The water reservoir is not seated firmly: Check that the water reservoir is firmly seated in its place on the back of the machine.
 - The machine is warming up/reaching the operating temperature: Please allow a short time for the machine to warm up before it dispenses.
 - The grind size is too fine: Let the brew time out and follow the recommended grind setting on your next brew.
 - The machine needs to be descaled: Follow the instructions under the Cleaning & Maintenance section.

Why is the espresso stream small/flowing slowly?

- There could be several reasons behind this:
- The grind size is too fine: Let the brew time out and follow the recommended grind setting on your next brew.
 - Basket cleanliness: Before grinding, ensure the basket is free of any clogs or debris that could impede the flow.
 - The machine needs to be descaled: Follow the instructions under the Cleaning & Maintenance section.

Why is the espresso stream flowing very fast?

- The grind size is too coarse: Let the brew time out and follow the recommended grind setting on your next brew.
- Coffee is tamped too lightly: When tamping, make sure to place the portafilter on a level surface. Place the assisted tamper inside the funnel and push down on it until you feel the tamper contact the funnel.

Why does the espresso run around the edge of the portafilter?

- Portafilter is not inserted into the group head correctly: Place portafilter into group head by aligning orange dot on portafilter with orange dot on group head. Fasten portafilter into group head until orange dot on portafilter aligns with lock arrow on group head.
- There are coffee grounds around the basket rim: Clean unwanted grounds from the edge of the basket and portafilter to ensure portafilter sits properly in group head.
- The group head seal needs to be replaced.

Frothing does not start.

- Machine has not reached operating temperature: Please allow a short time for the machine to warm up before frothing begins.
- Not enough water in the reservoir: Ensure the water reservoir is filled up to the min. line.
- The water reservoir is not seated firmly: Check that the water reservoir is firmly seated in its place on the back of the machine.
- Wand is not inserted down: Ensure the steam wand is inserted into the milk jug, with the milk jug properly seated on the platform.
- Not enough milk in the milk jug: Ensure milk is filled up to the min. line.

Coffee is not hot enough.

- Preheat the portafilter: Rinse the portafilter under hot water before grinding. Please make sure that the basket is completely dry before grinding.
- Preheat the cup: Rinse the cup under hot water before brewing to increase the temperature of the brew.
- Adjust water temperature: See the Adjusting Brew Temperature section.
- Use heated froth settings: All froth settings are heated except cold foam, which is denoted with a snowflake.

- The machine needs to be descaled: Follow the instructions under the Cleaning & Maintenance section.

My drink is too bitter/acidic.

- Match grind setting: Use the grind dial on the side of the machine to match the Current grind setting to the Recommended grind setting on the control panel before grinding.
- Change ratio: To increase/decrease the grounds-to-water ratio, please refer to the Additional Settings section.
- Change the brew temperature: For dark-roast beans, we recommend using the low or medium temperature setting. For medium- or light-roast beans, we recommend using the medium or high temperature setting.

Why am I not getting any crema?

- Coffee is tamped too lightly: When tamping, make sure to place the portafilter on a level surface. Place the assisted tamper inside the funnel and push down on the tamper until you feel it contact the funnel.
- The grind size is too coarse: Let the brew time out and follow the recommended grind setting on your next brew.
- Coffee beans are not fresh: Bean freshness will impact the crema quality. When purchasing coffee beans, it's best to buy a bag with a "Roasted On" date rather than a "Best Before" date to ensure quality and freshness. We recommend you use coffee beans within 20 days of the "Roasted On" date.
- Basket may be clogged/holes are blocked: Ensure you are cleaning the baskets frequently. Make sure none of the holes in the bottom of the basket are clogged with grounds.

WARRANTY REPAIR INFORMATION

If you need service on your unit and this product requires repair during the 90 days warranty period; please go to www.ConsumerServiceRefurbish.com or call the **Refurbished Product Service Center** at 602-946-3531 to obtain the required return authorization (RA) number. Pack the unit properly (the original carton is ideal for this purpose) along with a copy of your purchase receipt and a letter describing the problem. Send the unit freight prepaid and insured to:

Refurbished Product Service Center,
Attn: Customer Service Department 9043 Siempra Viva Rd Suite 110/120, San Diego CA, 92154

Your unit will be promptly repaired and returned to you. We will refuse to accept delivery of the returned unit unless the assigned RA number appears on the outside of the shipping carton.

Owner's Information (Keep for your permanent records)			
NAME: _____	ADDRESS: _____		
CITY: _____	STATE: _____	ZIP CODE: _____	
PHONE: _____	E-MAIL: _____		
MODEL: _____	SERIAL NO.: _____		

Why does the drip tray fill quickly?

- To ensure the machine maintains the ideal pressure for espresso, during a brew, some water will bypass into the main drip tray. This is normal.
- The machine will automatically purge water from the steam wand into the main drip tray after each froth. This is to clean the inside of the steam wand.
- The main drip tray is designed to hold the water bypass from the creation of up to 6 cappuccinos. **Why does the machine make a pulsing**